



NEW

SKYJACK™

INTRODUCING SKYJACK'S NEW
COMPACT RT SCISSORS

COMPACT ROUGH TERRAIN SERIES

Skyjack's new SJ6826RT and SJ6832RT models boast a maneuverable 68" wide stance with working heights of 32' and 38' respectively. Coming standard with a powerful dual fuel engine, cross over symmetrical 4WD, these RT's are driveable at full height with their 5' roll out deck extension fully extended, these RT's can tackle any job site obstacle with ease. With options such as: diesel engine and auto/independent leveling outriggers to name a few, the new Compact RT models make no compromises to the famous tough and reliable reputation of Skyjack rough terrain scissor family. While having a number of engineering upgrades, these 2 new models hold true to Skyjack's philosophy of keeping units as simple as possible for ease of maintenance. The newly designed manifold tilts out for easy access and the engine swings out completely for service via a single quick release latch.

One glance at the new Compact Rough Terrain Skyjack and you'll understand the strength of innovative design.



All Compact RT's come standard with 5 foot roll out deck extension and are driveable at full height with the deck extension fully extended.

SJ 6826 RT shown with optional auto/independent leveling outriggers



New spin-off hydraulic filter and tilt out hydraulic manifold offer easy access for maintenance and service.



90° swing out engine tray and accessible electric panel.

Dimensional Specifications	SJ6826RT	SJ6832RT
Work Height	32 ft.	38 ft.
Raised Platform Height	26 ft.	32 ft.
Lowered Platform Height	47 in.	53 in.
O/A Width	68 in.	68 in.
O/A Length	107 in.	107 in.
Stowed Height (rails up)	93.5 in.	99 in.
Stowed Height (rails down)	63.5 in.	69 in.
Platform Size (inside dimension)	56 x 98 in.	56 x 98 in.
Deck Extension	60 in.	60 in.
Ground Clearance	8 in.	8 in.
Wheelbase	80.5 in.	80.5 in.
Standard Technical Specifications		
Weight	6,400 lbs.	7,660 lbs.
Gradeability	50%	40%
Lift Time (with rated load)	41 sec	41 sec
Lower Time (with rated load)	30 sec	40 sec
Drive Speed (stowed)	4.5 mph	4.5 mph
Drive Speed (raised)	0.5 mph	0.5 mph
Maximum Drive Height	Full height deck out	Full height deck out
Capacity (overall)	1,250 lbs.	1,000 lbs.
Tire Size/ Type	12 x 26 Foam Filled	12 x 26 Foam Filled
Standard Equipment	Optional Equipment	
Cross Over Symmetrical (COS) 4WD	Flashing light	
60" roll out deck extension	Shop airline to platform	
90° swing out engine tray	800 watt AC inverter	
Tilt out hydraulic manifold	Auto/Independent leveling outriggers	
110V AC outlet on platform	Extra propane tank and bracket	
Foam filled rough terrain tires	Diesel engine (in lieu of std dual fuel)	

A WORD ABOUT THIS BROCHURE

This brochure is for illustrative purpose only and based on the latest information at the time of printing. Skyjack Inc. reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Consult the Operating Maintenance and Parts Manuals for proper procedures. Work platforms have been tested to comply with applicable ANSI and CSA standards as interpreted by Skyjack, Inc.